



DECLARATION OF PERFORMANCE

No. SU-4.0

- 1. Birch Plywood SVEZA PARQUET Type FSF with thickness of 9-21 mm (SVEZA PARQUET 9-21)
- 2. For internal use in humid conditions (uncoated) BS EN 636-2 NS as non-structural components BS EN 13986 : 2004+A1:2015 (4.5)
- 3. Manufacturer:

LLC "SVEZA Uralskiy"

1a Moskovskaya str., Uralskiy, Nytva District, Perm Region 617005, RUSSIA

- 4. System of assessment and verification of consistency of performance of the construction product according to BS EN 13986:2004+A1:2015 System 4
- 5. Declared performance:

| Essential characteristics | Performance | Designated technical specification |
|---|--|------------------------------------|
| Bonding quality (moisture resistance) | Class 3 | BS EN 636 : 2012, BS EN 314-2:1993 |
| Release of formaldehyde | E1 | BS EN 636 : 2012, Table 3 |
| Reaction to fire | Depending on thickness and end use conditions but not less than Class D-s2, d0 | BS EN 13986, Table 8 |
| Water vapour permeability | NPD | BS EN 12524; BS EN 13986, Table 9 |
| Airborne sound insulation | NPD | BS EN 13986, 5.10 |
| Sound absorption (not valid for external use) | NPD | BS EN 13986, Table 10 |
| Thermal conductivity (by mean density of 684 kg/m³) | NPD | BS EN 13986, Table 11 |
| Biological durability | NPD | BS EN 13986, 5.17 |
| Content of pentachlorophenol | < 5 ppm | BS EN 13986, 5.18 |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Uralskiy, 30 August 2021



Denis L. Maltsev Director of Branch "Uralskiy" of LLC "SVEZA-Les"

КАМЕНСКИХ М.А. на основании доверенности дов/8500-21-000041 от 11.08.2021 г