

DECLARATION OF PERFORMANCE No. ST-14.1

1. **Birch Plywood Type FSF with the thickness < 9 mm (FSF < 9)**
2. For internal use in humid conditions (uncoated) – BS EN 636-2 NS – and for external use (coated and with sealed edges)) – BS EN 636-3 NS – as non-structural components – BS EN 13986 : 2004+A1:2015 (4.5, 4.6)
3. Manufacturer: **LLC SVEZA Tyumen**
Kamchatskaya str. 196, Tyumen, 625034, Russian Federation
Tel/Fax +7 (3452) 63-77-65 (+2577) E-mail: vn.zablovskii@sveza.com
4. System of assessment and verification of consistency of performance of the construction product according to BS EN 13986:2004+A1:2015 – System 4
5. Declared performance:

<i>Essential characteristics</i>	<i>Performance</i>	<i>Designated technical specification</i>
Bonding quality (moisture resistance)	Class 3	BS EN 636 : 2012, BS EN 314-2:1993
Release of formaldehyde	E1	BS EN 636 : 2012, Table 3
Reaction to fire	Class E	BS EN 13986, Table 8
Water vapour permeability	NPD	BS EN 12524; BS EN 13986, Table 9
Airborne sound insulation	NPD	BS EN 13986, 5.10
Sound absorption (not valid for external use)	NPD	BS EN 13986, Table 10
Thermal conductivity (by mean density of 650 kg/m ³)	NPD	BS EN 13986, Table 11
Biological durability	NPD	BS EN 13986, 5.17
Content of pentachlorophenol	< 5 ppm	BS EN 13986, 5.18

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



N.A. Gorodetsky

Director of Branch “Tyumen” of LLC SVEZA-Les

Tyumen, 1 August 2021