



DECLARATION OF PERFORMANCE No. SUI-3.1

- 1. Birch Plywood Type FSF with the thickness < 9 mm (FSF < 9)
- 2. For internal use in humid conditions (uncoated) BS EN 636-2 NS and for external use (coated and with sealed edges)) BS EN 636-3 NS as non-structural components BS EN 13986 : 2004+A1:2015 (4.5, 4.6)
- 3. Manufacturer: JSC "SVEZA Ust-Izhora"

ul. Fanernaya 5, Pontonny, Saint Petersburg, 196643, RUSSIA

- 4. System of assessment and verification of consistency of performance of the construction product according to BS EN 13986:2004+A1:2015 System 4
- 5. Declared performance:

| Essential characteristics | Performance | Designated technical specification |
|---|-------------|------------------------------------|
| Bonding quality (moisture resistance) | Class 3 | BS EN 636 : 2012, BS EN 314-2:1993 |
| Release of formaldehyde | E1 | BS EN 636 : 2012, Table 3 |
| Reaction to fire | Class E | BS EN 13986, Table 8 |
| Water vapour permeability | NPD | BS EN 12524; BS EN 13986, Table 9 |
| Airborne sound insulation | NPD | BS EN 13986, 5.10 |
| Sound absorption (not valid for external use) | NPD | BS EN 13986, Table 10 |
| Thermal conductivity (by mean density of 674 kg/m³) | NPD | BS EN 13986, Table 11 |
| Biological durability | NPD | BS EN 13986, 5.17 |
| Content of pentachlorophenol | < 5 ppm | BS EN 13986, 5.18 |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Denis K. Alekseev Director of Branch «Ust-Izhora» of LLC «SVEZA-Les»

Saint Petersburg, 7 July 2021

