



DECLARATION OF PERFORMANCE No. SU-2.0

1. Birch Plywood Type FSF with the thickness 9-35 mm (FSF 9-35)

2. For internal use in humid conditions (uncoated) – BS EN 636-2 NS – and for external use (coated and with sealed edges)) – BS EN 636-3 NS – as non-structural components – BS EN 13986 : 2004+A1:2015 (4.5, 4.6)

3. Manufacturer:

LLC "SVEZA Uralskiy"

1a Moskovskaya str., Uralskiy, Nytva District, Perm Region 617005, RUSSIA

4. System of assessment and verification of consistency of performance of the construction product according to BS EN 13986:2004+A1:2015 – System 4

5. Declared performance:

Essential characteristics	Performance	Designated technical specification
Bonding quality (moisture resistance)	Class 3	BS EN 636 : 2012, BS EN 314-2:1993
Release of formaldehyde	E1	BS EN 636 : 2012, Table 3
Reaction to fire	Depending on thickness and end use conditions but not less than Class D-s2, d0	BS EN 13986, Table 8
Water vapour permeability	NPD	BS EN 12524; BS EN 13986, Table 9
Airborne sound insulation	NPD	BS EN 13986, 5.10
Sound absorption (not valid for external use)	NPD	BS EN 13986, Table 10
Thermal conductivity (by mean density of 684 kg/m³)	NPD	BS EN 13986, Table 11
Biological durability	NPD	BS EN 13986, 5.17
Content of pentachlorophenol	< 5 ppm	BS EN 13986, 5.18

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Uralskiy, 30 August 2021



Denis L. Maltsev Director of Branch "Uralskiy" of LLC "SVEZA-Les"

КАМЕНСКИХ М.А. НА ОСНОВАНИИ ДОВЕРЕННОСТИ ДОВ/8500-21-000041 ОТ 11.08.2021Г